

POWER DISTRIBUTION UNIT (PDU)

230Vac Input, L6-30P1 on 43.5 Power Cord, Qty 6 each L6-15R Output and Qty 2 each L630R on 24" Cords, Each Output having a Push Pull Circuit/Switch control, 1U9.5, Aluminum



Part # FA00395

Model # IPDUL630L620R2L615R6

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Power Distribution Unit (PDU)

IP Part #:	FA00395
IP Model #:	IPDUL630L620R2L615R6
Unit Description:	230Vac Input, L6-30P1 on 43.5 Power Cord, Qty 6 each L6-15R Output and Qty 2 each L630R on 24" Cords, Each Output having a Push Pull Circuit/Switch control, 1U9.5, Aluminum

SPECIFICATIONS

Power Rating (VA, Watts):	5750Va, 5750W
Input AC Voltage (AC Voltage, tolerance):	230Vac
Input DC Voltage (DC Voltage, tolerance):	N/A
Output AC Voltage (AC Voltage, tolerance):	230Vac
Output DC Voltage (DC Voltage, tolerance):	N/A
Enclosure Type & Size (type/rack unit, dimensions):	1U9.5, 1.72" x 17.0" x 9.5"
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum, IP Gray
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location, pin outs):	L6-30P on 43.5" Cord
Connector(s) DC Input (type, location, pin outs):	N/A
Connector(s) AC Output (type, location, pin outs):	6 each L6-15R; 2 each L6-30R On 24" Cord
Connector(s) DC Output (type, location, pin outs):	N/A
Connector(s) EBP/Charger (type, location, pin outs):	N/A
Temperature (operating, storage):	-20 to 50 Dec C
Humidity:	0-95% Non-Condensing
Conformal Coated PCBAs (yes/no):	N/A
Breaker & Switch Input (type, location, rating):	2P30A Switch/Circuit Breaker, On Front
Breaker & Switch AC Output (type, location, rating):	2P15A Push Pull x 6, 2P25A Push Pull x 2, All On Front
Breaker & Switch DC Output (type, location, rating):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Un-Bonded

ISO 9001: 2008 Certified

Mil Standards



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

