

UNINTERRUPTIBLE POWER SYSTEM (UPS)

Bright UPS 3000VA, 2600W, 120VAC 50/60Hz Input and 120VAC 60Hz Output, Double Conversion, On Line, High Temperature, Isolated, Rugged UPS with Power Factor Correction for Industrial Applications.



Part # FA10045

Model # IHT3000RM-I-2.6Kw-120VAC-Isol-120V-PFC-9BFB-3U26

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs, and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

ISO 9001: 2008 Certified

IntelliPower is committed to customer satisfaction by delivering power system solutions and services that meet or exceed customer requirements through design innovation and continuous improvement.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA10045
IP Model #:	IHT3000RM-I-2.6Kw-120VAC-Isol-120V-PFC-9BFB-3U26
Unit Description:	Bright UPS 3000VA, 2600W, 120VAC 50/60Hz Input and 120VAC 60Hz Output, Double Conversion, On Line, High Temperature, Isolated, Rugged UPS with Power Factor Correction for Industrial Applications.
SPECIFICATIONS	
Power Rating (VA, Watts):	3000VA, 2600 watts
Input AC Voltage (AC Voltage, tolerance):	120VAC -15% to +15%
Input DC Voltage (DC Voltage, tolerance):	NA
Input Frequency (Hz, tolerance):	50/60Hz
Input Max Current (Amps):	32.8 Amps
Output AC Voltage (AC Voltage, tolerance):	120VAC +/- 3%
Output DC Voltage (DC Voltage, tolerance):	NA
Output Frequency (Hz, follower/changer):	60Hz Frequency changer
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	Rack Mount 3U 5.25"H x 17"W X 26"D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front to rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	8 foot L5-30P Plug
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	6 NEMA 5-20R
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	Anderson
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V 10.5AH PbAcid
Battery Total Quantity:	9
Battery String Voltage:	108Volts
Battery String (number of strings, quantity per string)	1
Battery Minimum Run Time (approx. run time at #watts):	7 Min 2600 watts with UPS
Battery Mounting (hot swap/fixd):	Fixed
Temperature:	-10C to +50C
Humidity:	0 to 95%
PFC Feature:	Yes
Isolation (galvanic isolation/non-isolated):	Isolated
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	EMI Honey Comb Filters
Auto Start (manual start/auto start):	Auto start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 115%
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMP 3.3
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	N/A
Breaker & Switch Input (type, location):	2P35A
Breaker & Switch AC Output (type, location):	1P25A Push Reset
Breaker & Switch DC Output (type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded

ISO 9001: 2008 Certified

TAA Compliant



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

