


UNINTERRUPTIBLE POWER SYSTEM (UPS)

Double Conversion, Free Standing Tower On Line UPS System with Power Factor Correction.



FEATURES & BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs, and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

ISO 9001: 2008 Certified

IntelliPower is committed to customer satisfaction by delivering power system solutions and services that meet or exceed customer requirements through design innovation and continuous improvement.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

Part # FA00041

Model # IQ2000V-230-Isol-w/SpCom-3U23c

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

SPECIFICATIONS	
IP Part #:	FA00041
IP Model #:	IQ2000V-230-Isol-w/SpCom-3U23c
Unit Description:	Bright UPS Double Conversion Free Standing Tower On Line UPS System with Power Factor Correction.
Power Rating (VA, Watts):	2000 VA, 1400 W
Input AC Voltage (AC Voltage, tolerance):	230VAC (-23% +15%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50/60 Hz
Input Max Current (Amps):	11 Amps
Output AC Voltage (AC Voltage, tolerance):	230VAC (±3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	50/60Hz Follower
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	Tower, 5¼"W x 17"H x 23"D
Enclosure Material & Finish (aluminum/steel, finish):	Steel
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	1 each IEC-320-C14, rear panel
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	4 each IEC-320-C13, rear panel
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V7Ah Lead Acid
Battery Total Quantity:	5
Battery String Voltage:	60VDC
Battery String (number of strings, quantity per string)	1, 5
Battery Minimum Run Time (approx. run time at #watts):	5 minutes at 1400W
Battery Mounting (hot swap/fixed):	Fixed
Temperature:	0°C to +50°C operating
Humidity:	0-95%, non-condensing
PFC Feature:	Input Power Factor Correction
Isolation (galvanic isolation/non-isolated):	Galvanic Isolation
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	None
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 115%
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	RS232 DA-15 D-subminiature, rear panel
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	Relay Interface via a detachable 6" long cable
Breaker & Switch Input (rating, type, location):	Rocker switch on front panel
Breaker & Switch AC Output (rating, type, location):	N/A
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded



All Products Designed and Manufactured in the U.S.A.

ISO 9001: 2008 Certified

TAA Compliant



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com