

UNINTERRUPTIBLE POWER SYSTEM (UPS)

Bright UPS: 3000VA, 3000W, 120VAC 50/60Hz Input and 120VAC 60Hz Output



Part # FA00139

Model # IQ3000RM-I-3.0Kw-FC60-120V-9LBFb-3U22

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs, and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

ISO 9001: 2008 Certified

IntelliPower is committed to customer satisfaction by delivering power system solutions and services that meet or exceed customer requirements through design innovation and continuous improvement.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



SPECIFICATIONS	
IP Part #:	FA00139
IP Model #:	IQ3000RM-I-3.0Kw-FC60-120V-9LBF8-3U22
Unit Description:	Bright UPS: 3000VA, 3000W, 120VAC 50/60Hz Input and 120VAC 60Hz Output
Power Rating (VA, Watts):	3000VA, 3000W
Input AC Voltage (AC Voltage, tolerance):	120VAC (-15% +15%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50/60Hz (±5Hz)
Input Max Current (Amps):	39 Amps
Output AC Voltage (AC Voltage, tolerance):	120VAC (±3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	60Hz Changer
Output Sync Requirements:	(Synced within ±3Hz from the input frequency or fixed at 60Hz if outside of this range)
Enclosure Type & Size (type/rack unit, dimensions):	3U22
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	Terminal Block
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	10 each NEMA 5-20R
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V10.5Ah Lead Acid
Battery Total Quantity:	9
Battery String Voltage:	108VDC
Battery String (number of strings, quantity per string)	1, 9
Battery Minimum Run Time (approx. run time at #watts):	5 min. for 3000W
Battery Mounting (hot swap/fixed):	Fixed
Temperature:	0°C to +40°C operating
Humidity:	0-95%, non-condensing
PFC Feature:	Input Power Factor Correction
Isolation (galvanic isolation/non-isolated):	Non-Isolated
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	Dust filter on front panel
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 5% overload
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMP, RJ-45 Port
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	Relay Interface via a detachable 6” long cable
Breaker & Switch Input (type, location):	Rocker switch on front panel
Breaker & Switch AC Output (type, location):	Push to reset on rear panel
Breaker & Switch DC Output (type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Un-bonded

ISO 9001: 2008 Certified

TAA Compliant



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

