

## UNINTERRUPTIBLE POWER SYSTEM (UPS)



## FEATURES & BENEFITS

### Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

### Cutting Edge Technology

Our digital double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs, and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

### Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

### Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

### ISO 9001: 2008 Certified

IntelliPower is committed to customer satisfaction by delivering power system solutions and services that meet or exceed customer requirements through design innovation and continuous improvement.

To find out more about IntelliPower capabilities, please visit our website at [www.intellipower.com/capabilities](http://www.intellipower.com/capabilities).

Part # FA00263

Model # IQ3000VM-C-2.1kw-DiAC-  
Isol-120/230v-50/60-6BFB-3U24al

## CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA  
Tel: 714.921.1580 • Fax: 714.921.4023  
Email: [sales@intellipower.com](mailto:sales@intellipower.com) • [www.intellipower.com](http://www.intellipower.com)

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA00263
IP Model #:	IQ3000VM-C-2.1kw-DiAC-Isol-120/230v-50/60-6BFB-3U24al
Unit Description:	Rugged Double Conversion High Temperature Isolated Global Input & Output On-Line UPS
SPECIFICATIONS	
Power Rating (VA, Watts):	3000 VA, 2100 W
Input AC Voltage (AC Voltage, tolerance):	120 or 240 VAC, (-20% to +15%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50 or 60 Hz
Input Max Current (Amps):	31 Amps
Output AC Voltage (AC Voltage, tolerance):	120 or 240 AC, ( $\pm 3\%$ ), Selectable with Toggle Switch, Rear Panel
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	50 or 60 Hz, Follower
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	Vertical, 5.25"H x 17"W x 24"D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	1 each L6-30P on a 30 Amp 18" Pigtail Power Cord for 240VAC Inputs, Rear Panel 1 each L5-30P on a 12" Adapter Cord for 120VAC Inputs
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	6 each IEC-60320 C19, Rear Panel
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V8Ah, Lead Acid
Battery Total Quantity:	6
Battery String Voltage:	72 VDC
Battery String (number of strings, quantity per string)	1, 6
Battery Minimum Run Time (approx. run time at #watts):	5+ minutes at 2000 W
Battery Mounting (hot swap/fixe):	Fixed
Temperature:	-20°C to +40°C
Humidity:	0-95%, Non-Condensing
PFC Feature:	Yes
Isolation (galvanic isolation/non-isolated):	Galvanic Isolation
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/combinatio/grill):	Dust
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 105 to 110%
Conformal Coated PCBAs (yes/no):	No
Communications (SNMP2/SNMP3/RS232, type):	SNMP, Ethernet Jack, Rear Panel
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	N/A
Breaker & Switch Input (type, location):	Toggle Switch, Front Panel
Breaker & Switch AC Output (type, location):	Toggle Switch, Rear Panel, Selects 120 or 240 VAC Outputs
Breaker & Switch DC Output (type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded

ISO 9001: 2008 Certified

TAA Compliant



#### CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA  
 Tel: 714.921.1580 • Fax: 714.921.4023  
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

