

UNINTERRUPTIBLE POWER SYSTEM (UPS)

2000VA, 1500W, 120VAC or 240VAC, 50/60Hz Input and 120VAC, 60Hz or Selectable 50Hz, Synch's Freq Output, Double Conversion, Isolated, Global Input, Rugged, High Temperature On Line UPS with Front Panel Hot Swap Battery, Power Factor Correction and Additional Isolated EMI Filtered Auxiliary Outputs.



Part # FA00082

Model # IHT2000RM-M-1.5kw-DiAC-Isol-120v-FC60-5BHS-PFC-3U24

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA00082
IP Model #:	IHT2000RM-M-1.5kw-DiAC-Isol-120v-FC60-5BHS-PFC-3U24
Unit Description:	Bright UPS 2000VA, 1500W, 120VAC or 240VAC, 50/60Hz Input and 120VAC,60Hz or Selectable 50Hz, Synch's Freq Output, Double Conversion Isolated Global Input Rugged High Temperature On Line UPS with Front Panel Hot Swap Battery, Power Factor Correction and Additional Isolated EMI Filtered Auxiliary Outputs
Power Rating (VA, Watts):	2000VA, 1500W
Input AC Voltage (AC Voltage, tolerance):	AutoSelect, Global Input of 120VAC or 240VAC (90 to 138VAC or 190 to 265VAC)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50/60Hz (45 to 450Hz)
Input Max Current (Amps):	22 Amps
Output AC Voltage (AC Voltage, tolerance):	120VAC (±2%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	50/60Hz selectable
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	3U, 5.25"H x 17"W x 24 "D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	IEC-320-C20
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	4 ea NEMA 5-15/20R receptacles for UPS output 2 ea NEMA 5-15/20R receptacles for Aux output
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	Yes, EBP connector
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V9Ah Lead Acid
Battery Total Quantity:	5
Battery String Voltage:	60VDC
Battery String (number of strings, quantity per string)	1, 5
Battery Minimum Run Time (approx. run time at #watts):	6.4 min. for 1400W
Battery Mounting (hot swap/fixed):	Hot Swap
Temperature:	-20°C to +50°C operating; -40°C to 65°C Storage
Humidity:	0-95%, non-condensing
PFC Feature:	Input Power Factor Correction
Isolation (galvanic isolation/non-isolated):	Galvanic Isolation
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	EMI filters on all
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 15% overload
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	RS232 DE-9 D-sub port, Opto-isolated
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	N/A
Breaker & Switch Input (rating, type, location):	Toggle switch on front panel
Breaker & Switch AC Output (rating, type, location):	Push to reset on front panel
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded

ISO 9001: 2008 Certified

TAA Compliant



CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

