

## UNINTERRUPTIBLE POWER SYSTEM (UPS)

2500 VA, 2000 W, Global Auto Select 120 or 240 VAC, 50/60 Hz Input and 120 VAC, 50/60 Hz Output, Double Conversion On-Line, High Temperature, 5 each 12V10EB, Lithium Iron Phosphate, Hot Swap Battery Drawer, Rugged UPS with Power Factor Correction for Military Applications.



Part # FA10168

Model # IHT2500RM-M-2.0Kw- DiAC-Isol-120V-5LiFEBHS-2U24

## FEATURES AND BENEFITS

### Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

### Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

### Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

### Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

### Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at [www.intellipower.com/capabilities](http://www.intellipower.com/capabilities).

## CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA  
Tel: 714.921.1580 • Fax: 714.921.4023  
Email: [sales@intellipower.com](mailto:sales@intellipower.com) • [www.intellipower.com](http://www.intellipower.com)

All products designed and manufactured in the U.S.A.



<b>Uninterruptible Power System (UPS)</b>	
IP Part #:	FA10168
IP Model #:	IHT2500RM-M-2.0Kw- DiAC-Isol-120V-5LiFEBHS-2U24
Unit Description:	2500 VA, 2000 W, Global Auto Select 120 or 240 VAC, 50/60 Hz Input and 120 VAC, 50/60 Hz Output, Double Conversion On-Line, High Temperature, 5 each 12V10EB, Lithium Iron Phosphate, Hot Swap Battery Drawer, Rugged UPS with Power Factor Correction for Military Applications.
<b>SPECIFICATIONS</b>	
Power Rating:	2500 VA, 2000 Watts
Input AC Voltage 1:	120 or 240 VAC, (-20% +15%)
Input Frequency 1:	50 or 60 Hz, (+/- 5 Hz)
Input Max Current:	28.34 Amps
Output AC Voltage 1:	120 VAC, (+/-3%) at 2000 Watts
Output Frequency 1:	50 or 60 Hz, (+/-3 Hz), follower
Output Sync:	selectable or synced to input
Enclosure Type:	2U, rack mountable
Enclosure Dimensions:	English: 3.5 x 17 x 24 inch(Height x Width x Depth) Metric: 8.89 x 43.18 x 60.96 cm(Height x Width x Depth)
Enclosure Material and Finish:	aluminum, powder coated charcoal gray
Enclosure Airflow:	front to rear
Connector(s) AC Input 1:	1 each IEC 60320 C20
-position:	panel mounted, rear
Connector(s) AC Output 1:	4 each NEMA 5-20R
-position:	panel mounted, rear
Battery Type 1:	12.8V9.6Ah Lithium Iron Phosphate
Battery Quantity Total:	5
Battery Strings Quantity Total:	1
Battery Voltage per String:	64 VDC
Battery Runtime 1:	Approximately 15 minutes at 1500 Watts
Battery Mounting:	hot swap
Temperature Operating:	-20C to 50C (Celsius), -4F to 122F (Fahrenheit)
Humidity:	5 to 95% non-condensing
PFC Feature:	input power factor correction
Isolation:	isolated
Application:	ground
Fan Filters:	EMI
Auto Start:	inverter output configured to start automatically, manual start available in settings
Overload Action:	shutdown at 110%
Conformal Coating	included
Communications - Remote:	SNMPv3.X
Switches and Breakers AC Input 1:	2P20A, toggle
Switches and Breakers AC Output 1:	1 each 1P25A, push to reset
Neutral Bonding:	bonded

ISO 9001: 2008 Certified Facility

**CORPORATE HEADQUARTERS**

1746 N. Saint Thomas Circle • Orange, CA 92865 USA  
 Tel: 714.921.1580 • Fax: 714.921.4023  
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

