

UNINTERRUPTIBLE POWER SYSTEM (UPS)

IntelliPower Bright UPS: 3KVA, 3KW Double Conversion On Line Isolated 115VAC Input UPS, and simultaneous 120 and 240VAC 60Hz Output, Power Factor Correction, Extended Internal Batteries, SNMP Communications for Military Applications.



Part # FA10186

Model # IHT3000RM-M-3kw-115Vin-Isol-120-240Vac out-9BHS-3U26

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA10186
IP Model #:	IHT3000RM-M-3kw-115VIn-Isol-120-240Vac out-9BHS-3U26
Unit Description:	IntelliPower Bright UPS: 3KVA, 3KW Double Conversion On Line Isolated 115VAC Input UPS, and simultaneous 120 and 240VAC 60Hz Output, Power Factor Correction, Extended Internal Batteries, SNMP Communications for Military Applications.
Power Rating (VA, Watts):	3000 VA, 3000 Watts
Input AC Voltage (AC Voltage, tolerance):	115 VAC, (+/-15%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	40 to 70 Hz
Input Max Current (Amps):	39.92 Amps
AC Output Voltage #1 (AC Voltage, tolerance):	120VAC (+/-3%) @1500W
AC Output Voltage #2 (AC Voltage, tolerance):	240VAC, (+/-3%) @1500W
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	60 Hz, (+/-3 Hz), changer
Output Sync Requirements:	3U, rack mountable
Enclosure Type & Size (type/rack unit, dimensions):	English: 5.25 x 17 x 26 inch (Height x Width x Depth) Metric: 13.34 x 43.18 x 66.04 cm (Height x Width x Depth)
Enclosure Material & Finish (aluminum/steel, finish):	aluminum, powder coated charcoal gray
Enclosure Airflow (front to rear/front to side/other):	front to rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location, pin outs):	1 each MS3254L20-19P, on rear panel
Connector(s) DC Input (type, location, pin outs):	N/A
Connector(s) AC Output (type, location, pin outs): 1	1 each MS3452L20-19S, on rear panel
Connector(s) AC Output (type, location, pin outs): 2	1 each MS3452L20-19SW (90 Degree Clocking, 240V), on rear panel
Connector(s) DC Output (type, location, pin outs):	N/A
Connector(s) EBP/Charger (type, location, pin outs):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V8.5Ah Pb-Acid
Battery Total Quantity:	9
Battery String Voltage:	108VDC
Battery String (number of strings, quantity per string)	1
Battery Minimum Run Time (approx. run time at #watts):	6 minutes at 2000 Watts
Battery Run Current: (Start/End of Battery)	41.67A
Battery Mounting (hot swap/fixe):	Hot Swap
Temperature (operating, storage):	0°C to 50°C (Celsius), -4°F to 122°F (Fahrenheit)
Humidity:	5 to 95% non-condensing
PFC Feature:	input power factor correction
Isolation (galvanic isolation/non-isolated):	isolated
Application (shipboard/airborne/ground/all):	ground
Fan Filters (EMI/dust/comboination/grill):	EMI
Auto Start (manual start/auto start):	inverter output configured to start automatically, manual start available in settings
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	shutdown at 110%
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMP V 3.3
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	N/A
Breaker & Switch Input (rating, type, location):	2P40A toggle, on front panel
Breaker & Switch AC Output (rating, type, location):	1 each 1P15A (120V) & 1P7.0A (240V), push to reset on rear panel
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded
Note: If Non-Isolated Enter Un-Bonded	

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

