

UNINTERRUPTIBLE POWER SYSTEM (UPS)

3000VA, 3000W, 230VAC 60Hz Isolated Input, 230VAC 60Hz Output, Freq Changer, 9BHS (LiFePO4), 3U26, Steel, L6-30P Corded, RS232, L6-30R Corded.



Part # FA10199

Model # IHT3000RM-M-3.0Kw-230V-Isol-FC60-230V-9LifeBHS-3U26

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA10199
IP Model #:	IHT3000RM-M-3.0Kw-230V-Isol-FC60-230V-9LifeBHS-3U26
Unit Description:	3000VA, 3000W, 230VAC 60Hz Isolated Input, 230VAC 60Hz Output, Freq. Changer, 9BHS (LiFePO4), 3U26, Steel, L6-30P Corded, RS232, L6-30R Corded
SPECIFICATIONS	
Power Rating (VA, Watts):	3000VA, 3000W
Input AC Voltage (AC Voltage, tolerance):	230VAC (-20% +15%)
Input Frequency (Hz, tolerance):	50/60Hz (+/-5%)
Input Max Current (Amps):	21.2
Output AC Voltage (AC Voltage, tolerance):	230VAC (±3%)
Output Frequency (Hz, follower/changer):	60Hz Changer
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	3U26
Enclosure Material & Finish (aluminum/steel, finish):	Steel
Enclosure Airflow (front to rear/front to side/other):	Front to Rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location, pin outs):	1 each L6-30P on a 6ft Cord
Connector(s) DC Input (type, location, pin outs):	N/A
Connector(s) AC Output (type, location, pin outs):	1 each L6-30R on a 6ft Cord
Connector(s) EBP/Charger (type, location, pin outs):	Anderson
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	9.6Ah LiFe Iron Phosphate
Battery Total Quantity:	9
Battery String Voltage:	108
Battery String (number of strings, quantity per string)	1, 9
Battery Minimum Run Time (approx. run time at #watts):	4 hours @ 100Watts
Battery Run Current: (Start/End of Battery)	41.67
Battery Mounting (hot swap/fixed):	Hot Swap
Temperature (operating, storage):	-15°C to +50°C operating
Humidity:	0-95%, non-condensing
PFC Feature:	Input power factor correction
Isolation (galvanic isolation/non-isolated):	Galvanic Isolation
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	Dust Filter on front panel
Auto Start (manual start/auto start):	Auto start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 5 %
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	RS232 DE-9 D-sub port, Opto-isolated, Upsilon software and cable included
Breaker & Switch Input (rating, type, location):	2 pole 25AMP front panel
Breaker & Switch AC Output (rating, type, location):	2P15A located on rear panel
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Un-bonded
Note: If Non-Isolated Enter Un-Bonded	
Weight:	120lbs

ISO 9001: 2008 Certified Facility

Military Standards

CORPORATE HEADQUARTERS

 1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

