

UNINTERRUPTIBLE POWER SYSTEM (UPS)

1200 VA, 1000 W, 115 VAC Input, Double Conversion, Rugged, Isolated, High Temperature Rack Mount On-Line with 120 VAC at 60 Hz Output to provide Power Backup and Power Conditioning for Shipboard Applications.



Part # FA10306

Model # IHT1200RM-M-1KW-Isol-115v-60Hz-115v-NB-3U12

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA10306
IP Model #:	IHT1200RM-M-1KW-Isol-115v-60Hz-115v-NB-3U12
Unit Description:	1200 VA, 1000 W, 115 VAC Input, Double Conversion, Rugged, Isolated, High Temperature Rack Mount On-Line with 120 VAC at 60 Hz Output to provide Power Backup and Power Conditioning for Shipboard Applications.
SPECIFICATIONS	
Power Rating (VA, Watts):	1200 VA, 1000 W
Input AC Voltage (AC Voltage, tolerance):	115 VAC, (-20% +15%), Auto Select
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	60 Hz
Input Max Current (Amps):	14.32A
Output AC Voltage (AC Voltage, tolerance):	115 VAC, (±3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	60 Hz Follower
Output Sync Requirements:	Synced to within ±5Hz of Input Frequency
Enclosure Type & Size (type/rack unit, dimensions):	Rack Mountable 3U, 5.218"H x 16.25"W x 12.00"D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location, pin outs):	1 each 3 Position Screw Terminal Block, Rear Panel TB1-1 = H, TB1-2 = N and TB1-3 = Ground
Connector(s) DC Input (type, location, pin outs):	N/A
Connector(s) AC Output (type, location, pin outs):	1 each 3 Position Screw Terminal Block, Rear Panel TB2-1 = H, TB2-2 = N and TB2-3 = Ground
Connector(s) DC Output (type, location, pin outs):	No
Connector(s) EBP/Charger (type, location, pin outs):	1 each DBM9W4 Battery Cable Terminal, Rear Panel
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V8.5Ah Pb-Acid in EBP FA10307
Battery Total Quantity:	SEE EBP FA10307
Battery String Voltage:	60 VDC
Battery String (number of strings, quantity per string)	SEE EBP FA10307
Battery Minimum Run Time (approx. run time at #watts):	Approx. 30 min at 900W with EBP FA10307
Battery Run Current: (Start/End of Battery)	25ADC
Battery Mounting (hot swap/fixe d):	N/A
Temperature (operating, storage):	-15C to +55C Operating
Humidity:	0-95%, Non-Condensing
PFC Feature:	Input Power Factor Correction
Isolation (galvanic isolation/non-isolated):	Galvanic isolation
Application (shipboard/airborne/ground/all):	All
Fan Filters (EMI/dust/com bination/grill):	EMI
Auto Start (manual start/auto start):	Auto start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 15% Overload
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMP 3
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	Dry Contact Control, Emergency Power Off, EPO, only w/no Utility Present.
Breaker & Switch Input (rating, type, location):	Toggle Switch, Front Panel 2P15A
Breaker & Switch AC Output (rating, type, location):	Push to Reset, Front Panel 1P12A
Breaker & Switch DC Output (rating, type, location):	2P30A EPB Disconnect on top panel
Neutral Bonded to Ground (bonded/un-bonded/switch):	Toggle Switch, Top Panel
Note: If Non-Isolated Enter Un-Bonded	
If Switch, Factory Default Is:	Bonded

ISO 9001: 2015 Certified Facility

Military Standards

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

