

UNINTERRUPTIBLE POWER SYSTEM (UPS)

IHT, 6000Va, 4000W, dual 115 60Hz Isolated Input, 115Vac 60Hz Output. Freq Changer, EBP, 3U24.



Part # FA10310

Model # IHT6000RM-M-4.0kw-115VAC-Isol-FC60-115VAC-3U24-EBP

FEATURES AND BENEFITS

Rugged & Extreme Environments

All IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. Over the past 25 years, IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle • Orange, CA 92865 USA
Tel: 714.921.1580 • Fax: 714.921.4023
Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.



Uninterruptible Power System (UPS)	
IP Part #:	FA10310
IP Model #:	IHT6000RM-M-4.0kw-115VAC-Isol-FC60-115VAC-3U24-EBP
Unit Description:	IHT, 6000Va, 4000W, dual 115 60Hz Isolated Input, 115Vac 60Hz Output. Freq Changer, EBP, 3U24.
SPECIFICATIONS	
Power Rating (VA, Watts):	6000 VA, 4000 Watts
Input AC Voltage 1 (AC Voltage, tolerance):	115 VAC, (-7% +7%)
Input AC Voltage 2 (AC Voltage, tolerance):	115 VAC, (-7% +7%)
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency 1 (Hz, tolerance):	50 or 60 Hz, (+/- 5 Hz)
Input Frequency 2 (Hz, tolerance):	50 or 60 Hz, (+/- 5 Hz)
Input Max Current (Amps):	57.9 Amps
Output AC Voltage (AC Voltage, tolerance):	115 VAC, (+/-3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	60 Hz, (+/-3 Hz), changer
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	3U, rack mountable; English: 5.25 x 17 x 24 inch (Height x Width x Depth)
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum, powder coated charcoal gray
Enclosure Airflow (front to rear/front to side/other):	Front to rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input 1 (type, location, pin outs):	1 each MS3452L22-2P, Panel mounted, rear
Connector(s) AC Input 2 (type, location, pin outs):	1 each MS3452L22-2P, Panel mounted, rear
Connector(s) DC Input (type, location, pin outs):	N/A
Connector(s) AC Output 1 (type, location, pin outs):	2 each L5-20R, Panel mounted, rear
Connector(s) AC Output 2 (type, location, pin outs):	4 each L5-20R, 12" Pigtail mounted, rear
Connector(s) DC Output (type, location, pin outs):	N/A
Connector(s) EBP/Charger (type, location, pin outs):	1 each Elcon4-21-4, Panel mounted, rear
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V8.5Ah Pb-Acid with EBP FA10214
Battery Total Quantity:	N/A
Battery String Voltage:	96 VDC
Battery String (number of strings, quantity per string)	2 each for connecting to 16 batteries in EBP FA10214
Battery Minimum Run Time (approx. run time at #watts):	Approximately 12 minutes at 3200 Watts with EBP FA10214
Battery Run Current: (Start/End of Battery)	31.25A Ea PCBA 62.5A total
Battery Mounting (hot swap/fixd):	None internal, 1 each external battery pack (EBP)
Temperature (operating, storage):	-10°C to 50°C (Celsius), 14°F to 122°F (Fahrenheit)
Humidity:	5 to 95% non-condensing
PFC Feature:	Input power factor correction
Isolation (galvanic isolation/non-isolated):	Isolated
Application (shipboard/airborne/ground/all):	Shipboard
Fan Filters (EMI/dust/combination/grill):	EMI
Auto Start (manual start/auto start):	Auto Start
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 115%
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMPv3.X
Communications – Special (CIP/VMware ESX/ESXi/other):	N/A
Communications – Discrete (relay/opto, description):	N/A
Breaker & Switch Input (rating, type, location):	2P60A, toggle, Qty. 2
Breaker & Switch AC Output (rating, type, location):	6 each 1P20A Push to Reset
Breaker & Switch DC Output (rating, type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Switch
Note: If Non-Isolated Enter Un-Bonded	
If Switch, Factory Default Is:	Bonded

ISO 9001:2015 Certified Facility

Military Standards

CORPORATE HEADQUARTERS

 1746 N. Saint Thomas Circle • Orange, CA 92865 USA
 Tel: 714.921.1580 • Fax: 714.921.4023
 Email: sales@intellipower.com • www.intellipower.com

All products designed and manufactured in the U.S.A.

