

UNINTERRUPTIBLE POWER SYSTEM (UPS)

Rugged, Double Conversion, High Temperature, Galvanic Isolation, Global Input with 120VAC Output. Lead Acid batteries. True On-Line UPS and Power Conditioning/Conversion System with Power Factor Correction for Military Applications in a Rack Mount Enclosure with Front Panel Hot Swap Battery Drawer.



Part # FA00422

Model # IHT2000RM-M-1.5kw-DiAC-Isol-120v-5060-5BHS-2U26

FEATURES AND BENEFITS

Rugged & Extreme Environments

All AMETEK IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

AMETEK IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing AMETEK IntelliPower's building block methodology, more product features and functionality are provided without having to extend lead times or change proven designs. For over 32 years, AMETEK IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within AMETEK IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). AMETEK IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy, Marines and Coast Guard.

To find out more about AMETEK IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle Orange, CA 92865 USA
 Tel: 714-921-1580 Fax: 714-921-4023
 Email: ca-ora-sales@ametek.com www.intellipower.com

All products designed, manufactured & supported in the USA.



Uninterruptible Power System (UPS)	
IP Part #:	FA00422
IP Model #:	IHT2000RM-M-1.5kw-DiAC-Isol-120v-5060-5BHS-2U26
IP Description:	Rugged, Double Conversion, High Temperature, Galvanic Isolation, Global Input with 120VAC Output. Lead Acid batteries. True On-Line UPS and Power Conditioning/Conversion System with Power Factor Correction for Military Applications in a Rack Mount Enclosure with Front Panel Hot Swap Battery Drawer.
INPUT RATINGS	
Input AC Voltage (AC Voltage, tolerance):	120 or 240 VAC, (-25% +15%)
Input DC Voltage (AC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50 or 60 Hz, (+/- 5 Hz)
Input Max Current (Amps):	21.9 Amps
PFC Feature:	input power factor correction
Breaker & Switch AC Input (type, location):	2P25A Toggle on Front Panel
OUTPUT RATINGS	
Power Rating (VA, Watts):	2000 VA, 1500 Watts
Output AC Voltage (AC Voltage, tolerance):	120 VAC, (+/-3%)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	50 or 60 Hz, (+/-3 Hz), follower
Output Sync Requirements:	Synced to input
Isolation (galvanic isolation/non-isolated):	Isolated
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded
Output AC Breaker & Switch (type, location):	1P20A Push to Reset on Rear Panel
Output Overload – Shutdown or Bypass:	Bypass at 115%. Resets with ON button after overload is cleared.
MECHANICAL	
Enclosure Type & Size (type/rack unit, dimensions):	Rackmount 2U, 3.5" x 17.0" x 26" (Height x Width x Depth)
Enclosure Material & Finish (aluminum/steel finish):	Aluminum, IP Gray
Enclosure Airflow (front to rear/front to side/other):	Front to Rear
Nominal Weight +/- lbs.:	85Lbs
Fan Filters (EMI/dust/comboination/grill):	Dust
Conformal Coated PCBAs (yes/no):	Yes
INTERFACE COMMUNICATIONS	
Serial Data Stream (SNMP v3/RS232, type):	RS232 and USB
Special (CIP, VMware ESX/ESXi/Other):	N/A
Discrete (Relay/Opto, Description):	N/A
ADDITIONAL ELECTRICAL FEATURES AND CONTROLS/INTERFACE	
Auto Start (manual start/auto start):	Yes
Cold Start Switch (Yes/No):	No
CONNECTORS	
Connector(s) AC Input (type, location):	IEC 60320 C20 On Rear Panel
Connector(s) AC Output (type, location):	6 each NEMA 5-20R on Rear Panel
Connector(s) EBP/Charger (type, location):	N/A
Overload – Shutdown or Bypass (shutdown/bypass, %):	Bypass at 115%. Resets with ON button after overload is cleared.
BATTERIES	
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	12V 9Ah Lead Acid
Battery Total Quantity:	5
Battery String Voltage:	60 VDC
Battery String (number of strings, quantity per string):	1 String of 5 Batteries
Battery Minimum Run Time (approx. run time at #watts):	15 Minutes at 600 Watts
Battery Mounting (hot swap/fixe):	Hot Swap
External Battery Module (EBM) PN:	N/A

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle Orange, CA 92865 USA
 Tel: 714-921-1580 Fax: 714-921-4023
 Email: ca-ora-sales@ametek.com www.intellipower.com

All products designed, manufactured & supported in the USA.



EMI and ENVIRONMENTAL	
Application (shipboard/airborne/ground/all):	Ground
Temperature (Operating):	-10°C to 50°C (Celsius)
Humidity:	5 to 95% non-condensing

ISO 9001:2015 Certified Facility | Designed to Meet Mil Standards | Specifications subject to change without notice

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle Orange, CA 92865 USA
Tel: 714-921-1580 Fax: 714-921-4023
Email: ca-ora-sales@ametek.com www.intellipower.com

All products designed, manufactured & supported in the USA.

