

UNINTERRUPTIBLE POWER SYSTEM (UPS)

1500VA, 1250W, 85-265VAC, 50/60Hz Input and 120VAC, 60Hz Output (Optional 240VAC Output)



Part # FA10507

Model # IHT1500RM-M-1.25Kw-WRGlobal-Isolated-FC60-120-LiFeHS-3U16

FEATURES AND BENEFITS

Rugged & Extreme Environments

All AMETEK IntelliPower systems utilize circuit boards, chassis and components that are **specifically designed for extreme environments**. In today's marketplace, repackaged commercial products are often billed as "rugged" and/or "built for harsh environments". Each component in our systems is specifically selected or designed based upon proven performance in harsh indoor and outdoor applications.

Cutting Edge Technology

Our digital, double conversion on-line UPS, power conditioner and frequency/voltage converter solutions utilize high-efficiency power switching and galvanic isolation which provides **ideal electrical output performance**. Systems are available with global voltage inputs & outputs, AC inputs & outputs and DC inputs & outputs. You will be able to utilize any power source.

AMETEK IntelliPower offers power management software along with many standard communications protocols such as SNMP with OID and MIB Support, RS-232, Ethernet/IP – Common Industrial Protocol (CIP), MODBUS and Dry/Discrete Contacts. The sum total of these technological features equals the ultimate protection for your electronic equipment.

Robust Product Portfolio

No other UPS company offers **2,000+ variations**. Utilizing AMETEK IntelliPower's building block methodology, more product features and functionality are provided; without having to extend lead times or change proven designs. For over 30 years, AMETEK IntelliPower has developed its electronics hardware, firmware, embedded software and enclosure technology in house, which provides us with a unique capability to meet virtually any of your application requirements to include completely sealed systems.

Designed and Manufactured in the USA

The engineering and technological expertise within AMETEK IntelliPower has enabled us to develop and field test products since 1988 to **100% user satisfaction**. For you, this translates into shorter lead times from design to shipping as well as personalized service and support. Our mission is to provide you with the highest standard of customer support and quality control.

Military Standards Compliance

All product configurations are designed and manufactured to **meet military standards**. Systems have been and can also be certified by independent labs. Many standards are met in our standard build practices, some notable standards include MIL-STD-461F (Electromagnetic Interference EMI), MIL-STD-464C (Electromagnetic Environmental Effects EME), MIL-STD-1275D (DC Electrical Power Systems), MIL-STD-901D (Shock), MIL-STD-167-A (Vibration), MIL-STD-810G (Environmental; Altitude, Temperature, Humidity, Fungus, Sand & Dust, Rain), and MIL-STD-1399-300B (Interface requirements for AC devices; Voltage Transients (spikes), Frequency Transients, Harmonics, Power Factor). AMETEK IntelliPower products are used in a wide range of key military programs within the Army, Air Force, Navy and Marines.

To find out more about AMETEK IntelliPower capabilities, please visit our website at www.intellipower.com/capabilities.

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle Orange, CA 92865 USA
 Tel: 714-921-1580 Fax: 714-921-4023
 Email: ca-ora-sales@ametek.com www.intellipower.com

TAA Compliant. All products designed and manufactured in the USA.
 9001:2015 ISO Certified Facility
 Military Standards



Uninterruptible Power System (UPS)	
IP Part #:	FA10507
IP Model #:	IHT1500RM-M-1.25Kw-WRGlobal-FC60-120VAC-LiFeHS-3U16
IP Description:	1500VA, 1250W, 85-265VAC 50/60Hz Input, 120VAC and 60Hz Output (Optional 240VAC Output)
SPECIFICATIONS	
Power Rating (VA, Watts):	1500 VA, 1250 W
Input AC Voltage (AC Voltage, tolerance):	85 to 265VAC
Input DC Voltage (DC Voltage, tolerance):	N/A
Input Frequency (Hz, tolerance):	50/60 Hz, (±5%)
Input Max Current (Amps):	20 Amps
Output AC Voltage (AC Voltage, tolerance):	120VAC, (±3%) Selectable (Optional 240VAC Output)
Output DC Voltage (DC Voltage, tolerance):	N/A
Output Frequency (Hz, follower/changer):	60 Hz, Changer
Output Sync Requirements:	N/A
Enclosure Type & Size (type/rack unit, dimensions):	Rack Mountable 3U x 8.5" W x 16" D
Enclosure Material & Finish (aluminum/steel, finish):	Aluminum
Enclosure Airflow (front to rear/front to side/other):	Front-to-rear
Enclosure – Special (IP65/Zone 1):	N/A
Connector(s) AC Input (type, location):	1 each IEC C14 inlet
Connector(s) DC Input (type, location):	N/A
Connector(s) AC Output (type, location):	3 each NEMA 5-15R, Rear Panel
Connector(s) DC Output (type, location):	N/A
Connector(s) EBP/Charger (type, location):	N/A
Battery Type (rating, PbAcid/Pure PbAcid/Lithium Iron):	Lithium Iron Phosphate
Battery Total Quantity:	1
Battery String Voltage:	89.6 VDC
Battery String (number of strings, quantity per string)	28SIP
Battery Minimum Run Time (approx. run time at #watts):	11 minutes at 1000 watts
Battery Mounting (hot swap/fixed):	Hot Swap
Temperature:	Operating: -20°C to 50°C; Storage: -30°C to +65°C
Humidity:	0-95%, Non-Condensing
PFC Feature:	Yes
Isolation (galvanic isolation/non-isolated):	Isolated
Application (shipboard/airborne/ground/all):	Ground
Fan Filters (EMI/dust/comboination/grill):	Grill
Auto Start (manual start/auto start):	Auto Start (Manual start configurable)
Cold Start Switch (yes/no):	No
Overload – Shutdown or Bypass (shutdown/bypass, %):	Shutdown at 20% Overload
Conformal Coated PCBAs (yes/no):	Yes
Communications (SNMP2/SNMP3/RS232, type):	SNMP v.3, Ethernet Jack, Rear Panel, 10, 100, 1000 Gigabit Capable
Breaker & Switch Input (type, location):	Toggle Switch, Front Panel 2P20A Hydraulic Magnetic
Breaker & Switch AC Output (type, location):	IP15A Push to Reset
Breaker & Switch DC Output (type, location):	N/A
Neutral Bonded to Ground (bonded/un-bonded/switch):	Bonded

ISO 9001:2015 Certified Facility | TAA Compliant | Military Standards

CORPORATE HEADQUARTERS

1746 N. Saint Thomas Circle Orange, CA 92865 USA
 Tel: 714-921-1580 Fax: 714-921-4023
 Email: ca-ora-sales@ametek.com www.intellipower.com

TAA Compliant. All products designed and manufactured in the USA.
 9001:2015 ISO Certified Facility
 Military Standards

